



Item	Specification
Frequency Rating	DC to 6GHz
Nominal Impedance	50 ohm
Temperature Range	-40 to +90 degree C
Voltage Rating	250V r.m.s
Contact Resistance	20m ohm max
Withstanding Voltage	AC 300V
Insulation Resistance	500M ohm min
V.S.W.R	DC~3GHz 1.5max
	3~6GHZ 1.7max
Insertion Loss	DC~3GHZ 1.5dB max
	3~6GHz 2.0dB max
Durability	10,000 cycles

11	FERRULE	BRASS	1	GOLD
10	CONTACT BODY	PHOSPHOR BRONZE	1	GOLD
09	INSULATOR	TEFLON	1	
08	BODY	BRASS	1	GOLD
07	CENTER PIN	BRASS	1	GOLD
06	INSULATOR	TEFLON	1	
05	SPRING	STAINLESS	1	
04	CENTER PIN	PHOSPHOR BRONZE	1	GOLD
03	BODY	BRASS	1	GOLD
02	INSULATOR COVER	POM	1	
01	COVER	BRASS	1	GOLD
NO	DESCRIPTION	MATERIAL	Q'TY	FINISH

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

PPOJECTION

照片框

ORDER INFORMATION

RFS-PCR-xxx-LF
SERIES | | LEADFREE
113:1.13mm
137:1.37mm
90°
CRIMP
PLUG

DESCRIPTION: