



Note:

1. Electrical Data:

- 1-1. Frequency Range: DC-6GHz
- 1-2. Impedance: 50 Ohms
- 1-3. VSWR: DC ~ 3GHz < 1.3
DC3 ~ 6GHz < 1.6

2. Mechanical Data:

- 2-1. Durability (Mating/Unmating): 500 CYCLES.
- 2-2. Contact Force (Mating/Unmating): 0.5N

NO.	ITEM NAME	MATERIAL	FINISH	Q'TY	REMARK
4	HEAT SHRINK TUBE			2	
3	CABLE OD ϕ 1.37			1	COLOR: BLACK
2	SMA JACK STR	BRASS	GOLD	1	
1	QE3000 PLUG	BRASS	GOLD	1	

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. \pm
.X \pm
.XX \pm
.XXX \pm
ANG \pm

PJECTION

照片框

ORDER INFORMATION

RFSSMA-1R1S137-E30C-LF

SERIES

LEADFREE

300mm

MALE TO FEMALE

1.37mm

RT/ST

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: RF Cable Test Probe R/A to SMA Jack STR
Cable OD:1.37mm L=300mm Black For MM8430