



PART LIST

No.	DESCRIPTION	MATERIAL & TREATMENT
01	RG-174 COAXIAL CABLE	PVC JACKET COAXIAL CABLE
02	PLUG OUTER CONTACT	BRASS WITH GOLD PLATING
03	PLUG MALE CONTACT	BRASS WITH GOLD PLATING
04	PLUG INSULATOR	TEFLON
05	PLUG FERRULE	BRASS WITH GOLD PLATING
06	PLUG CRIMPING SLEEVE	BRASS WITH GOLD PLATING
07	HEAT SHRINKABLE TUBING	POLYETHYLENE

CHARACTER

SPECIFICATIONS :

1. MECHANICAL CHARACTERISTICS :
MATING/UNMATING : 500 CYCLES

ELECTRICAL CHARACTERISTICS :

IMPEDANCE : 50 OHMS
FREQUENCY RANGE : 0~6 GHz
OPERATING VOLTAGE : AC 100V/DC 100V
CONTACT RESISTANCE : 100 MILLIOHMS MAX.
DIELECTRIC WITHSTANDING VOLTAGE :
150 VAC FOR 1min. CURRENT LEAKAGE 1mA MAX.

INSULATION : RESISTANCE : 1000 MEGOHMS MIN.

ENVIRONMENTAL CHARACTERISTICS :
TEMPERATURE RANGE : -25° TO 85°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PROJECTION

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

照片框

ORDER INFORMATION

RFTX1-1S1X174-M20C-LF
SERIES ST
LEADFREE
200mm
MALE
RG 174

DESCRIPTION: