



PIN OUT

RJ45 8P8C PLUG		RJ45 8P8C JACK	
1	ORANGE/WHITE	1	
2	ORANGE	2	
3	GREEN/WHITE	3	
6	GREEN	6	
4	BLUE	4	
5	BLUE/WHITE	5	
7	BROWN/WHITE	7	
8	BROWN	8	

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

P PROJECTION

照片框

ORDER INFORMATION

RJX2-080824C5EPE-E30C-LF

SERIES

8PIN TO 8 PIN

24 AWG

CAT-5E

PANEL

300mm

LEADFREE

MALE TO FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: RJ45 PLUG TO RJ45 JACK

***CONSTRUCTION:

- 1.CABLE: * UTP UL CM(4PR/24#) OD:5.1 CAT-5E 350 MHZ BLACK COLOR JACKET.
- CONNECTORS:
- 2.RJ45 PLUG: * RJ45 PLUG: 8P8C ONE-PIECE TYPE(#104-2E).
* HOUSING: PC MATERIAL,TRANSPARENT COLOR,UL94V-2 RATED.
* CONTACT: PHOSPHOR BRONZE WITH 50U GOLD PLATED.
- 3.RJ45 JACK: * RJ45 JACK: 8P8C JACK WITH PCB SOLDER TYPE.
* HOUSING: PBT+GLASS FIBRE,BLACK COLOR,UL94V-0 RATED.
* CONTACT: PHOSPHOR BRONZE WITH GOLD FLASH OVER NICKEL .
* PCB.
* SHELL: COPPER ALLOY WITH NICKEL PLATED.
* MOLDED: BLACK PVC 45P .
- 4.NUT: * NUT: M3 7.0*3.2 BRASS WITH ZINC PLATED.
- 5.TEST: * CT: 2 Ohm. IS: 5M Ohm DC300V,0.1S.
* DUALABILITY: 500 MATING CYCLES MIN.
* INSERTION AND WITHDRAWAL: 20N MAX(IEC60603-7)
- 6.PACKING: * PACK EACH CABLE IN A POLY BAG.
- 7.MATERIAL: * MATERIAL WITH RoHS GRADE.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X.±
.X±
.XX±
.XXX±
ANG±

PPOJECTION 

照片框

ORDER INFORMATION

RJX2-080824C5EPE-E30C-LF

SERIES

8PIN TO 8 PIN

24 AWG

PANEL

CAT-5E

300mm

LEADFREE

MALE TO FEMALE

DESCRIPTION: RJ45 PLUG TO RJ45 JACK