



SPECIFICATION:

CABLE: 1. COMPONENT:

- A. Size of conductors : STP CAT.5e 24AWG(7*0.20) Round Cable .
- B. Color coded insulation : white/orange-orange, white/green-green, white/blue-blue, white/brown-brown, + Drain .
- C. Diameter of electric : 1.0±0.05mm.
- D. UL style no. of single : (30v, 60°c).
- E. Number of twist pairs : Four pairs.

2. JACKET MATERIAL. : PVC

- A. Overall diameter : Ave 6.0mm
- B. Color. : GREY

PLUG: 1. TYPE : Modular U.S. R 8p8c type, golden plate: 50u" Shielded.

2. MATERIAL : PC UL 94v-2

BOOT: : PVC S.R.

JACK: 1. Cat5E Shielded Keystone jack 90°c , gold plated 50u" .

2. Color. : WHITE.

WIRING: 568B

P1	COLOR	P2
1	WH-OR	1
2	ORANGE	2
3	WH-GR	3
6	GREEN	6
4	BLUE	4
5	WH-BL	5
7	WH-BR	7
8	BROWN	8
SHELL	DRAIN	SHELL

NOTE: ☒ TWISTED PAIR



PART NO. RJX2-0808CER1FF-E25C

RoHS Compliant

DWG NO. RJX2-0808CER1FF-E25C

CHECKED BY CY

TOLERANCES ARE

DESCRIPTION:

FILE NO.

DRAWING BY

.X ± 0.2

AREA

REVISIONS

HK

DATE

UNIT / mm

SCALE 1:1

PROJECTION

.XX ± 0.1

.XXX ± AWG

煜倫股份有限公司