



Performance:

Meets C5e EIA/TIA 568B Standard.

Materials:

Body : ABS & Chromium Plated

JACK : 8P8C 50 micro inches gold plated

PCB : FR-4 / UL-94V0

Electrical Specifications:

Insulation Resistance : 500M ohms (min.)

Contact Resistance : 20m ohms (max.)

Current Rating : 1.5 Amps

DC Resistance : 0.1 ohms (max.)

Withstanding Voltage : 1000 VAC RMS @ 60Hz / 1 min.

Mechanical Specifications:

Jack Insertion Cycle : Over 2000 Cycles (min.)

Operation Temperature : -40 °C ~ +70 °C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ± 1.00

.X ± 0.20

.XX ± 0.15

.XXX ±

ANG ±

PPOJECTION



ORDER INFORMATION

RJX2-FSC5EPX48CC-0808-LF

SERIES

FEMALE TO FEMALE

NON

CAT.5E

NON

CHROMIUM
LONG 48.0mm

8P8C

LEADFREE

NON PANEL

DESCRIPTION: C5e INLINE COUPLER FTP

www.morethanall.com