



**Performance:**

Meets C5e EIA/TIA 568B Standard.

**Materials:**

Body : Fireproof ABS UL-94V0

JACK : 8P8C 50 micro inches gold plated

PCB : FR-4 / UL-94V0

**Electrical Specifications:**

Insulation Resistance : 500M ohms (min.)

Contact Resistance : 20m ohms (max.)

Current Rating : 1.5 Amps

DC Resistance : 0.1 ohms (max.)

Withstanding Voltage : 1000 VAC RMS @ 60Hz / 1 min.

**Mechanical Specifications:**

Jack Insertion Cycle : Over 2000 Cycles (min.)

Operation Temperature : -40 °C ~ +70 °C

**RoHS Compliant**

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ± 1.00

.X ± 0.20

.XX ± 0.15

.XXX ±

ANG ±

PPOJECTION



**ORDER INFORMATION**

RJX2-FSC5EPX48WH-0808-LF

SERIES

LEADFREE

8P8C

WHITE

LONG 48.0mm

NON PANEL

CAT.5E

FEMALE TO FEMALE

DESCRIPTION: C5e INLINE COUPLER UTP