



Waterproof Rate: IP67

Material:
Contact Plating: 6U" gold plating
Contacts: Bronze
Housing: PA6BG33
Panel: Zinc Alloy
Electrical:
Contact Resistance: $\leq 10\text{m}\Omega$
Insulation Resistance: $\geq 10\text{M}\Omega$
Current rating: 1.5A
Voltage rating: 125V
Data transfer rate: Cat6A
Compliant with TIA/EIA 586B, IEC11801.
Mechanical:
Operating: 750 Cycles Min.

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

TOLERANCES ARE

X. ± 0.50

.X ± 0.38

.XX ± 0.25

.XXX ± 0.10

ANG $\pm 3^\circ$

PPOJECTION

照片框

ORDER INFORMATION

RJX2-FSC6APQ28BK-0808-LF

SERIES

FEMALE TO FEMALE

8P8C

BLACK

28 AWG

CAT.6A

PANEL SQUARE

LEADFREE

DESCRIPTION: Metal Waterproof D Type Cat6A Rj45 Coupler Socket