









Performance:

Meets C6 EIA/TIA 568B Standard.

Materials:

Body : Fireproof ABS UL-94V0
Metallic Case : Metal
Jack : 8P8C 50 micro inches gold plated
PCB : FR-4 / UL-94V0

Electrical Specifications:

Insulation Resistance : 500M ohms (min.)
Contact Resistance : 20m ohms (max.)
Current Rating : 1.5 Amps .
DC Resistance : 0.1 ohms (max.)
Withstanding Voltage : 1000 VAC RMS @ 60Hz / 1 min.

Mechanical Specifications:

Jack Insertion Cycle : Over 2000 Cycles (min.)

Operation Temperature : -40 ℃ ~ +70 ℃

RoHS Compliant

MORETHANALL PCB CONNECTORS Cable ASSEMBLIES
煜倫股份有限公司
www.morethanall.com

DRAWING BY CY		TOLERANCES ARE
CHECKED BY GENIUS		X. ± .X ± 0.20 .XX ± 0.15 .XXX ± 0.10 ANG ±
UNIT / mm	SCALE 1 : 1	
DATE		
SIZE A4	PPOJECTION	



ORDER INFORMATION

RJX2-FSC6PN28FM-0808-LF

- RJX2 — SERIES
- FSC — FEMALE TO FEMALE
- 6 — CAT.6
- P — PANEL
- N — LONG 28mm
- 28 — FULL METAL
- FM — FULL METAL
- 0808 — 8P8C
- LF — LEADFREE

DESCRIPTION: C6 INLINE COUPLER FTP 50u