








SCALE 1/1



Specification :

Material :

1. Plastic Housing : ABS+PC, UL 94V-0, Black color.
2. RJ45 Jack Insert : Polycarbonate, UL 94-HB, Transparent color.
3. RJ45 Jack Shield : Bronze with Nickel plated.
4. RJ45 Jack Contact material & finished :
 - 4-1. Phosphor Bronze with 50-60 micro-inch Nickel plated.
 - 4-2. Contact area : Min. 3 mm 50 micro-inch Gold plated.

Performance :

- a. Insertion Force : 900 gms for 8 contacts.
- b. Retention Strength : 7.7 kgs between Jack and Plug.
- c. Operation Temperature : -40°C to 80°C.
- d. Durability : 750 cycles Plug-Jack mating and unmating test, insertion cycles at 20 cycles/minute max. Contact resistance test per 100 cycles.
- e. The Cat.6 performance is in compliance with the ANSI/TIA/EIA 568 B.2-1 standard.

RoHS Compliant

TOLERANCES ARE

照片框

ORDER INFORMATION

RJX2-FSC6PN35FM-0808-LF

SERIES LEADFREE

FULL METAL
LONG 35.2mm
PANEL
CAT.6
FEMALE TO FEMALE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PPOJECTION

DESCRIPTION: Cat.6 Inline Coupler Keystone Jack, Shielded.