



Front Panel Jack Only Clearance
W/O Latch Feature

Single Panel-Latch Clearance
Panel Thickness 1.60mm

Electrical:
 1.Voltage Rating:125 Vac Rms.
 2.Current Rating:1.5 Amp.
 3.Contact Resistance:40 Milliohms Max.
 4.Insulation Resistance:1000 Megohms Min @500 Vdc.
 5.Dielectric Strength:1000 Vac Rms 60Hz, 1Min.

Mechanical:
 1.Operating:750 Cycles Min.

Environmental:
 1.Storage:-40°C To +85°C.
 2.Opertion:-20°C To +75°C.
 Mates With Modular Plug Conforming
 To FCC Part 68, Subpart F.

Materials:
 Shielded: *Stainless Steel.*
 Plastic Housing: *Engineering Thermoplastic*
Flammibility Rating UL 94V-0.
 Contacts: *Thickness Phosphor Bronze*
 Plating: *Gold Plating Over Nickel In Contact.*

RoHS Compliant



焯倫股份有限公司

PART NO. RJX2-FSCEPN27FM-0808		CHECKED BY CY		TOLERANCES ARE X ± 0.50 .X ± 0.38 .XX ± 0.25 .XXX ± 0.10 ANG ± 3°	DESCRIPTION:		
DWG NO. RJX2-FSCEPN27FM-0808		DRAWING BY					
FILE NO.		PROJECTION		AREA	REVISIONS	DATE	
UNIT / mm	SCALE 1:1						