



ELECTRICAL PERFORMANCE:

- 1. Impedance : 50 ohms
- 2. Frequency Range : 0 ~ 3GHz
- 3. Working Voltage : AC60V Maximum
- 4. Dielectric Withstanding Voltage : AC200V Maximum
- 5. Insulator Resistance : 500 Megohms Minimum

4	RP-SMA ST. JACK	D704-300A1	GOLD	1
3	HEAT SHRINK TUBE	22D001-001		1
2	RG 316/CABLE	AC0316-A		1
1	RP-SMA R/A PLUG	D600-900A	GOLD	1
ITEM	DESCRIPTION	PART NUMBER	FINISHED	Q'TY

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1:1

DATE

SIZE A4

X. ±

.X ±

.XX ±

.XXX ±

ANG ±

PPOJECTION

照片框

ORDER INFORMATION

RPSMAX2-1R1S316-E50C-LF

SERIES

LEADFREE

500mm

MALE TO FEMALE

Rg316

RT/ST

DESCRIPTION: RP-SMA R/A PLUG TO RP-SMA ST. JACK TYPE FOR RG316 50.0 CM CABLE