



ELECTRICAL PERFORMANCE:

- 1.Impedance : 50 ohms
- 2.Frequency Range : 0 ~ 3GHz
- 3.Working Voltage : AC60V Maximum
- 4.Dielectric Withstanding Voltage : AC200V Maximum
- 5.Insulator Resistance : 500 Megohms Minimum

3	50 OHM RP-SMA ST.	D700-900A	GOLD	1
2	RG 316/CABLE	AC0316-A		1
1	RP-SMA R/A PLUG	D600-900A	GOLD	1
ITEM	DESCRIPTION	PART NUMBER	FINISHED	Q'TY

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT / mm

SCALE 1:1

.XX±

DATE

.XXX±

ANG±

照片框

ORDER INFORMATION

RPSMAX2-1R1S316-M50C-LF

SERIES

LEADFREE

500mm

MALE TO MALE

Rg316

RT/ST

煜倫股份有限公司

www.morethanall.com

SIZE A4

PJECTION

DESCRIPTION: RP-SMA R/A PLUG TO RP-SMA ST. PLUG TYPE FOR RG316 50.0 CM CABLE