



MODEL	A	B	C	D	E
RPTNC-PC-58 (58U)	1.05	5.6	6.5	3.2	4.5
RPTNC-PC-59 (59U)	0.75	6.6	7.5	4.1	5.5
RPTNC-PC-6 (6U)	1.2	7.6	8.6	5.1	6.5

NO	DESCRIPTION	QTY	ITEM NO.	MATERIAL	PLATING
1	BODY	1	T-A11F.G.A-ROHS	BRASS	NICKEL 100μ" MIN.
2	DIELECTRIC	1	D-070066	DELRIN	-
3	CENTER PIN	1	T-241F.G.A-ROHS	BRASS	GOLD 3-5μ" MIN.
4	FERRULE	1	F-06.07.08001-ROHS	BRASS	NICKEL 100μ" MIN.
5	SHELL	1	S-14003-ROHS	BRASS	NICKEL 100μ" MIN.
6	RETAINING RING	1	CW-12002-ROHS	BRASS	NICKEL 100μ" MIN.
7	GASKET	1	G-10001	RUBBER	-

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±

.X ±

.XX ±

.XXX ±

ANG ±

PPOJECTION

照片框

ORDER INFORMATION

RPTNC-PC-xx-LF

SERIES

LEADFREE

58:RG 58

59:RG 59

CRIMP
PLUG

DESCRIPTION: