



Wafer:

Available in 2 through 12 circuits
 Polarized with locking ribs
 Insulator : PBT UL94V-0
 Mate with Leoco 5011 socket

Specifications

- ◆ Current rating: 16A AC,DC
- ◆ Voltage rating: 380V AC,DC
- ◆ Temperature rating:-40°C to +110°C
- ◆ Contact Resistance: 20mΩ Max.
- ◆ Insulation Resistance: 1,000MΩ Min.
- ◆ Withstanding Voltage: 1,800V AC/minute

RST50-PDB-xy-LF
 LEADFREE

RoHS Compliant

PCB layout

MORETHANALL
 CONNECTORS
 ASSEMBLIES

煜倫股份有限公司

PART NO. RST50-PDB-xy

DWG NO. RST50-PDB-xy

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X ± 0.2
 .XX ± 0.1
 .XXX ±
 AWG

DESCRIP TION:				
AREA	REVISIONS	HK	DATE	

* Top side view

TYPE	0A	0B	0C	0D	0E	0F	0G	0H	0I	0K	0L	0M	0N	0O	0P
KEY/LOCK 2-way															

0Q	80

TYPE	0A	0B	0C	0D	0E	0F	0G	0H	0I	0K	80	81
KEY/LOCK 3-way												

TYPE	0A	0B	0C	0D	0E	0F	0G	0I	02
KEY/LOCK 4-way									

03	04	05	80	81	82

TYPE	0A	0B	0C	0D	05	06	80	81
KEY/LOCK 5-way								

83	84

TYPE	0A	0B	0C	0D	0E	01
KEY/LOCK 6-way						

04	06	14	80	81

TYPE	0A	0B	1B	0C	03
KEY/LOCK 7-way					

04	14	34	80	81

TYPE	0C	0D	08	10	80
KEY/LOCK 8-way					

81

TYPE	0A	0B	0C	0D
KEY/LOCK 9-way				

08	80	81

TYPE	0A	01	02	80
KEY/LOCK 10-way				

TYPE	0A	0B	0C	01
KEY/LOCK 11-way				

13	80

TYPE	80
KEY/LOCK 12-way	



PART NO. RST50-

DWG NO. RST50-

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X ± 0.2
.XX ± 0.1
.XXX ±
AWG

DESCRIPTION:

AREA

REVISIONS

HK

DATE

煜倫股份有限公司