



$\phi d2 : \phi 5.3 \pm 0.2$
 $\phi d3 : \phi 10.0 \pm 0.2$
 $a : 8.0 \pm 0.5$
 $L : 16.0 \pm 1.0$
 $\phi d1 : \phi 4.5 \pm 0.3$
 $C : 8.0 \text{ (min)}$
 $S : 1.1$

單位 UNIT : MM

規 格 \ SPECIFICATION			
品名 PART NO.		標準包裝 STANDARD PACKING	500 PCS
材質 MATERIAL	Copper	表面處理 SURFACE TREATMENT	Tin-Plated
附銅套 DOUBLE CRIMP		最大電流 MAX. Current Rating	62A
絕緣體 INSULATION		最大電壓 MAX. Voltage Rating	
適用電線 APPLICABLE WIRES	8 AWG 10.0 mm ²	耐溫 AMBIENCE TEMPERATURE	

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
X, ±
.XX ±
.XXX ±
ANG ±

PPOJECTION

照片框

ORDER INFORMATION

RT-X53-08-LF
SERIES | LEADFREE
8 AWG
ID:5.3mm
NON PVC

DESCRIPTION: