



$\phi d2$: $\phi 6.5 \pm 0.3$
 $\phi d3$: $\phi 12.0 \pm 0.3$
 a : 11.0 ± 0.6
 L : 25.0 ± 1.2
 $\phi d1$: $\phi 7.5 \pm 0.6$
 C : 12.0 (min)
 S : 1.5

規 格 \ SPECIFICATION			
品名 PART NO.		標準包裝 STANDARD PACKING	500 PCS
材質 MATERIAL	Copper	表面處理 SURFACE TREATMENT	Tin-Plated
附銅套 DOUBLE CRIMP		最大電流 MAX. Current Rating	115A
絕緣體 INSULATION		最大電壓 MAX. Voltage Rating	
適用電線 APPLICABLE WIRES	4 AWG 25 mm ²	耐溫 AMBIENCE TEMPERATURE	

RoHS Compliant

TOLERANCES ARE

煜倫股份有限公司

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, \pm
 X, \pm
 $.XX, \pm$
 $.XXX, \pm$
 ANG, \pm

PJECTION

照片框

ORDER INFORMATION

RT-X65-04-LF
 SERIES | LEADFREE
 | 04 AWG
 | ID:6.5mm
 NON PVC

DESCRIPTION:

www.morethanall.com