



a	: 5.0	± 0.5
C	: 4.5	min
Ød1	: Ø2.3	± 0.25
Ød2	: Ø8.4	± 0.22
d3	: 14.0	± 0.22
L	: 17.0	± 0.5
S	: 0.80	

單位 UNIT : mm

品名 PART NO.		標準包裝 STANDARD PACKING	1000 PCS
端子材質 TERMINAL MATERIAL	COPPER	表面處理 SURFACE TREATMENT	Tin-Plated
絕緣材質 INSULATION MATERIAL		電流 MAX.CURRENT RATING	27 A
絕緣顏色 INSULATION COLOR		電壓 MAX.VOLTAGE RATING	
適用電線 APPLICABLE WIRES	16-14 A.W.G. 1.5-2.5 mm ²	溫度 AMBIENCE TEMPERATURE	
銅材厚度 THICKNESS	0.80 mm	附銅管 DOUBLE CRIMP	

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

PPOJECTION

照片框

ORDER INFORMATION

RT-X84-14-LF
SERIES | LEADFREE
14~16 AWG
ID:8.4mm
NON PVC

DESCRIPTION: