



Recommended P.C.B Layout

MATERIAL

Contact Pin : Phosphor Bronze

Insulator : NY6T UL94-V0 

SPECIFICATION

Current Rate : 1 AMP

Insulation Resistance : $5000M\Omega$ Min.

Contact Resistance : $20m\Omega$ Max.

Dielectric Voltage : AC 500V for one minute

Operation Temperature : -40°C to $+105^{\circ}\text{C}$

POLES	DIM A	DIM B	POLES	DIM A	DIM B
			21	42.00	40.00
2	4.00	2.00	22	44.00	42.00
3	6.00	4.00	23	46.00	44.00
4	8.00	6.00	24	48.00	46.00
5	10.00	8.00	25	50.00	48.00
6	12.00	10.00	26	52.00	50.00
7	14.00	12.00	27	54.00	52.00
8	16.00	14.00	28	56.00	54.00
9	18.00	16.00	29	58.00	56.00
10	20.00	18.00	30	60.00	58.00
11	22.00	20.00	31	62.00	60.00
12	24.00	22.00	32	64.00	62.00
13	26.00	24.00	33	66.00	64.00
14	28.00	26.00	34	68.00	66.00
15	30.00	28.00	35	70.00	68.00
16	32.00	30.00	36	72.00	70.00
17	34.00	32.00	37	74.00	72.00
18	36.00	34.00	38	76.00	74.00
19	38.00	36.00	39	78.00	76.00
20	40.00	38.00	40	80.00	78.00

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ±
ANG ± 3°

PPOJECTION 

照片框

ORDER INFORMATION

S-D43-2Xxx-LF
SERIES | LEADFREE
2X02:04 WAY
2X40:80 WAY
HIGH 4.3mm
DIP 180°

DESCRIPTION: FEMALE HEADER 2.0*2.0mm STRAIGHT TYPE, DUAL ROWS HEIGHT 4.3mm