







Specifications
 Current Rating: 2.0Amp
 Insulation Resistance: 1000MΩMin.
 Dielectric Withstanding Voltage: 500VAC
 Contact Resistance: 20mΩMax.
 Operating Temperature: -40°C to +105°C
 Materials
 Contact Material: Phosphor Bronze
 Insulator Material: High Temperature Thermoplastic, UL 94V-0 LCP or the equivalent material

Recommended P.C.Board Layout
 (Tolerance: ±0.05)



MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

TOLERANCES ARE

X. ± 0.30


.X ± 0.25

.XX ± 0.15

.XXX ± 0.10

ANG ±

PPOJECTION



ORDER INFORMATION

S-V76PC-2Xxx-LF

SERIES
 180°SMT
 LEADFREE
 2X03:06WAY
 2X40:80WAY
 CAP POST
 HIGH 7.6mm

DESCRIPTION: 2.00 FEMALE HEADER DUAL ROWS SMT TYPE CONNECTOR