



TOLERANCE: ± 0.05 ,
RECOMMENDED PCB LAYOUT
(TOP VIEW)

NOTE:

- MATERIAL:
HOUSING: LCP WITH 30% GF, UL 94V-0, BLACK COLOR.
CONTACTS: PHOSPHOR BRONZE.
BOARDLOCKS: BRASS.
- FINISH:
CONTACTS: GOLD FLASH PLATED ON CONTACT AREA, [100 μ] MIN..
BRIGHT-TIN ON SOLDER TAIL, WITH ENTIRE CONTACT UNDERPLATED [50 μ] MIN.. NICKEL.
BOARDLOCKS: [100 μ] MIN. BRIGHT-TIN OVER [50 μ] MIN. NICKEL ON ENTIRE BOARDLOCK.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, \pm
.X \pm 0.30
.XX \pm 0.25
.XXX \pm 0.15
ANG \pm 2°

PJECTION

照片框

ORDER INFORMATION

SATA-SWB022Z-7+15-LF
SERIES | | | | LEADFREE
7+15 PIN
CLIP
HIGH 2.2mm
BOTTOM CONTACT
FEMALE
90°SMT

DESCRIPTION: SATA 7+15P 板上短脚SMT