

**SPECIFICATIONS**

BARRIER MATERIAL : THERMOPLASTIC ( UL 94V-0 ),BLACK  
 TERMINALS : TIN PLATED BRASS  
 SCREWS : NICKEL PLATED STEEL  
 WIRE RANGE AWG : 16-22 STR.  
 RATING : 15 AMPERES,300 VAC  
 INSULATION WITHSTANDS VOLTAGE AC 2000V/MIN  
 INSULATION RESISTANCE 500M OHM OR MORE AT DC 500V

**DIMENSION: ±0.5**

POLE	2	3	4	5	6	7	8	9	10	11	12	13	14	15				
A	18.5	26.75	14.25	43.25	51.5	59.75	68	76.25	84.5	92.75	101	109.3	117.5	125.8				
B	8.25	16.5	24.75	43.25	41.25	49.5	57.75	66	74.25	82.5	90.75	99	107.3	115.5				
POLE	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	
A	134	142.25	150.5	158.75	167	175.25	183.5	191.75	200	208.25	216.5	224.8	233	241.3	249.5	257.8	266	
B	123.75	132	140.25	148.5	156.75	165	173.25	181.5	189.75	198	206.25	214.5	222.8	231	239.3	247.5	255.8	

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS


UNIT/mm SCALE 1:1

DATE

SIZE A4

X. ±  
 .X ±  
 .XX ±  
 .XXX ±  
 ANG ±

PJECTION



**ORDER INFORMATION**

TBB082-R-xx-LF

SERIES | LEADFREE  
 02~32WAY  
 DIP 90°

DESCRIPTION: