



2P~6P增加防脫卡點

NOTES 1:

- UL Standard :
- 1.Rating: 300V 8A
  - 2.Insulation Withstands Voltage:  
AC 2000V at 1 minute
  - 3.Using Temperature Range:  
-40°C~+115°C
  4. Screw Torque Value:0.19N·m
  - 5.Suitable Electric Wire:AWG 28~14

IEC Standard:

- 1.Rating: 320V 14A
2. Rate Impulse Voltage: 2500V
- 3.Insulation Resistance:  
500MΩ or more at DC500V
4. Material Group : I
5. Pollution Degree : 2
6. Overvoltage Category: II
7. Using Temperature Range:  
-40°C~+110°C
8. Screw Torque Value: 0.2N·m
- 9.Suitable Electric Wire: 0.2~1.5mm²

NOTES 2:

1. RoHS compliance
- 2.Strip Length:6~7mm

5	BASE HOUSING	PA	UL94-V0 GREEN
4	CLAMP	COPPER ALLOY	Tin Plated
3	WIRE CAGE	COPPER ALLOY	M2/Ni Plated
2	SCREW	STEEL	M2/Zn Plated
1	TOP HOUSING	PA	UL94-V0 GREEN
ITEM	NAME OF PART	MATERIAL	NOTES

Total Pitch Tolerances		Normal Dimension Tolerances	
0~30	±0.20	0~30	±0.25
over 30~53	±0.25	over 30~53	±0.30
over 53~70	±0.30	over 53~70	±0.35
over 70~90	±0.35	over 70~90	±0.44
over 90~115	±0.44	over 90~115	±0.55
over 115~150	±0.55	over 115~150	±0.70
over 150~200	±0.70	over 150~200	±0.85
over 200~250	±0.85	over 200~250	±1.00
over 250~320	±1.00	over 250~320	±1.20

P	2	3	4	5	6	7	8	9	10	11	12
U	3.81	7.62	11.43	15.24	19.05	22.86	26.67	30.48	34.29	38.10	41.91
V	8.41	12.22	16.03	19.84	23.65	27.46	31.27	35.08	38.89	42.70	46.51
P	13	14	15	16	17	18	19	20	21	22	
U	45.72	49.53	53.34	57.15	60.96	64.77	68.58	72.39	76.20	80.01	
V	50.32	54.13	57.94	61.75	65.56	69.37	73.18	76.99	80.80	84.61	

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ± 0.30

.X ± 0.30

.XX ± 0.20

.XXX ± 0.10

ANG ± 1°

PPOJECTION

照片框

ORDER INFORMATION

TBH038-SVCB-xx-LF

SERIES

LEADFREE

02-22WAY

BOTTOM SIDE

CAGE

SCREW 180°

FEMALE

DESCRIPTION: