



P.C.B LAYOUT
TOP VIEW

Material:

- Item 1 Terminal housing: Thermoplastic (UL 94V-0)
- Item 2 Clamp: Brass Ni plated
- Item 3 Wire guard solder pin: Brass Tin plated
- Item 4 Terminal screw: Steel Zinc plating"-slot type

Electrical cULus / VDE

- Voltage rating: 300VAC / 450V
- Current rating: 20A / 24A
- Wire range: 0.2-2.5mm
- Solid wire(AWG): 12-30
- Stranded wire(AWG): 12-30
- Torque: 3.5 Lb-In / 0.5 N.m
- Screw: M3
- Wire strip length: 6-7mm
- Withstanding Voltage: 1.6KV / 2.5KV
- Operating temperature: -40°C to +105°C
- Assembly temperature: -5°C to +100°C
- Soldering temperature: 260°C±5°C/5 Sec
- Safety Approval:
- Critical dimension:

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X. ± 0.50

CHECKED BY GENIUS

.X ± 0.30

UNIT / mm

SCALE 1 : 1

.XX ± 0.10

DATE

.XXX ±

ANG ± 1°

煜倫股份有限公司

www.morethanall.com

SIZE A4

PJECTION

照片框

ORDER INFORMATION

TBH050-D19EE-04-LF

SERIES

LEADFREE

04 WAY

EMPTY#DUAL

HIGH 19.0mm

DIP180°

DESCRIPTION: 7P Horizontal solid block (180D wire inlet)-----Without cover, Omit 2,4,6P