

Material:

- Item ① metal housing: Steel
- Item ② Insulator(housing): Thermoplastic (UL94V-0)
- Item ③ Wire guard: PhBz(CuSn),Tin plated.
- Item ④ Terminal screw: Steel Zinc plating "--" slot type

Electrical:

- |                          |                 |
|--------------------------|-----------------|
|                          | cULus           |
| ● Voltage rating:        | 300V            |
| ● Current rating:        | 20A             |
| ● Wire range:            |                 |
| ● Solid wire(AWG):       | 12-30           |
| ● Stranded wire(AWG):    | 12-30           |
| ● Torque:                | 3.5 Lb-In.      |
| ● Screw:                 | M2.5            |
| ● Wire strip length:     | 8-9mm           |
| ● Withstanding Voltage:  | 1.6KV           |
| ● Operating temperature: | -30°C to +105°C |

POLE		2	3	4	5	6	7	8	9	10	11	12	
A		13.24	20.86	28.48	36.10	43.72	51.34	58.96	66.58	74.20	81.82	89.44	
B		7.62	15.24	22.86	30.48	38.10	45.72	53.34	60.96	68.58	76.20	83.82	
Tol.		±0.10					±0.15						
POLE	13	14	15	16	17	18	19	20	21	22	23	24	
A	97.06	104.68	112.30	119.92	127.54	135.16	142.78	150.40	158.02	165.64	173.26	180.88	
B	91.44	99.06	106.68	114.30	121.92	129.54	137.16	144.78	152.40	160.02	167.64	175.26	
Tol.		±0.20						±0.30					

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

P PROJECTION



ORDER INFORMATION

TBHO76-SH-xx-LF  
SERIES | LEADFREE  
02~24WAY  
H TYPE  
FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: