

P.C.B. LAYOUT


N = Number of poles
 Dim A = N x 9.52
 Dim B = (N-1) x 9.52

	Dim A	Dim B
2-6p	±0.20	±0.20
7-11p	±0.30	±0.30
12-16p	±0.40	±0.40

Material

- Terminal body
- (metal housing): Brass(CuZn)
- Terminal screw: Steel Zinc plating "-" slot type
- Contacts: Brass
- Surface of solder tail: Tin plated
- Insulator (housing): Thermoplastic (UL94V-0)

Electrical

- Voltage rating: 300VAC
- △ Current rating: 30A
- Wire range:
- △ Solid wire(AWG): 10-24
- △ Stranded wire(AWG): 10-24
- △ Torque(Lb-In): 8.9
- Screw: M3.5
- Wire strip length: 6-7mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 245°C±10°C/5 Sec
- Safety Approval:  us

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PPOJECTION 

X, ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±



ORDER INFORMATION

TBH95-A21-xx-LF

SERIES | LEADFREE
 | 02-24WAY
 | HIGH 12.0mm
 | SLANT DIP

DESCRIPTION: