

- NOTES:
 1. Rating: 15A
 2. Insulation Resistance: 500MΩ or more at DC500V
 3. Using Temperature Range: -40°C~+105°C
 4. RoHS Compliance

P	2	3	4	5
A	5.00	10.00	15.00	20.00
B	7.80	12.80	17.80	22.80

Total Pitch Tolerances		Normal dimension Tolerances	
0-30	±0.20	0-30	±0.25
over 30-53	±0.25	over 30-53	±0.30
over 53-70	±0.30	over 53-70	±0.35
over 70-90	±0.35	over 70-90	±0.44
over 90-115	±0.44	over 90-115	±0.55
over 115-150	±0.55	over 115-150	±0.70
over 150-200	±0.70	over 150-200	±0.85
over 200-250	±0.85	over 200-250	±1.00
over 250-320	±1.00	over 250-320	±1.20

2	JUMPER SLIDE	COPPER ALLOY	Tin PLATED
1	HOUSING	PA66	UL94-V0
ITEM	NAME OF PART	MATERIAL	NOTES

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1:1

DATE

SIZE A4

PPOJECTION

X, ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±



ORDER INFORMATION

TBR050-MJ-xx-LF

SERIES LEADFREE
 02-05 WAY
 J TYPE
 MALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: