



P1	P2
1 (RED)	
2 (WHITE)	
3 (GREEN)	
4 (BLACK)	

ELECTRICAL PROPERTIES:

1. 100% Open Short Mis -Wire Test
2. Contact Resistance:3 ohm max
3. Insulation Resistance: 10mega ohm min
4. Hipot test:DC 100V 10ms

③	PVC 45P 黑色 (ROHS)	6G
②	USB AM 30u'' 壳镀镍 白胶芯 (ROHS)	1PCS
①	UL2725 #28/1P+#28/2C+AE OD:3.5 BLACK (ROHS)	1PCS
NO.	DESCRIPTION	Q'TY

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

TOLERANCES ARE

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PPOJECTION

照片框

ORDER INFORMATION

UBX1-4A002V28-M92C-LF

SERIES

LEADFREE

920mm

MALE

28AWG

2.0 REV

4 PIN A TYPE

DESCRIPTION: USB AM TO OPEN L=92cm