



ELECTRICAL PROPERTIES:

1. 100% OPEN SHORT MIS-WIRE TEST
2. Contact Resistance: 10ohm max
3. Insulation Resistance: 20mega ohm MIN
4. Hipot test:DC 300V 5ms

|       |       |
|-------|-------|
| P1    | P2    |
| 1     | RED   |
| 2     | WHITE |
| 3     | GREEN |
| 4     | BLACK |
| SHELL | DRAIN |

| NO. | Description                                      | Q'TY | Unit |
|-----|--|------|------|
| 5   | NUT: M3.0 (配十字型SCREW2PCS)                        | 2    | pcs  |
| 4   | LDPE MOLDING, 30P                                | 4    | g    |
| 3   | PVC MOLDING, 30P BLACK                           | 8    | g    |
| 2   | CONNECTOR: USB B MALE GOLD G/F,WHITE COLOR       | 1    | pcs  |
| 1   | CABLE:NOUL 28AWG*1P+24AWG/2C+AE OD:3.5 PVC BLACK | 1    | pcs  |

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1:1

DATE

SIZE A4

X.±  
.X±  
.XX±  
.XXX±  
ANG±

PPOJECTION

照片框

ORDER INFORMATION

UBX1-4B002428PE-F5F-LF

SERIES

4 PIN B TYPE

24.28AWG

PANEL EAR

FEMALE

1524mm

LEADFREE

DESCRIPTION: USB B M TO OPEN L:5FT BLACK