



ELECTRICAL PROPERTIES:

1. 100% OPEN SHORT MIS-WIRE TEST
2. Contact Resistance: 10ohm max
3. Insulation Resistance: 20mega ohm MIN
4. Hipot test:DC 300V 5ms

P1	P2
1	RED
2	WHITE
3	GRENN
4	BLACK
SHELL	DRAIN

6	PVC MOLDING, 45P BLACK	6	g
5	NUT: M3.0 (配十字型SCREW2PCS)	2	pcs
4	LDPE MOLDING, 30P	4	g
3	PVC MOLDING, 30P BLACK	8	g
2	CONNECTOR: USB B MALE GOLD G/F,WHITE COLOR	1	pcs
1	CABLE:NOUL 28AWG*1P+24AWG/2C+AE OD:3.5 PVC BLACK	1	pcs
NO.	Description	Q'TY	Unit

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X.±
.X±
.XX±
.XXX±
ANG ±

PPOJECTION

照片框

ORDER INFORMATION

UBX1-4B1X2428PE-M5F-LF

SERIES | | | | | LEADFREE
4 PIN B TYPE | SR | 24.28 AWG | 1524mm
MALE
PANEL EAR

DESCRIPTION: USB B M TO OPEN+SR L:5FT BLACK