



PIN OUT:

P1		P2
1	red(24awg)	1
2	white(28awg)	2
3	green(28awg)	3
4	black(24awg)	4
shell	drain	shell

ITEM	PART NO.	DESCRIPTION	REMARK
1	5075A-02-02-30-F1	USB A MALE SOLDER TYPE GOLD 30U"	1
2	5075AF-04-M-30-F1	USB A FEMALE SOLDER TYPE GOLD 30U"	1
3	810B64USB2824B4.7BG3	UL 2725 28AWG*1P+24AWG*2C+AEB(64%) OD:4.7MM COLOR BEIGE	2.0REV
4	827-PVC-45P-BG	45P PVC MOLDING COLOR BEIGE	

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PPOJECTION

照片框

ORDER INFORMATION

UBX2-4A4A2V28-E9F-LF

SERIES

LEADFREE

2750mm

MALE TO FEMALE

28 AWG

2.0 RVE

4 PIN A TYPE TO 4 PIN A TYPE

DESCRIPTION: USB 2.0RVE CABLE