

ELECTRONIC TEST:
 1.OPEN/SHORT/INTERMITTE:100%.
 2.INSULATION RESISTANCE:20MΩ.
 3.CONTACT RESISTANCE:3Ω
 4.HI-POT:300V DTAGE.

PIN ASSIGNMENT

AM	AF	ODDOR
1 ———	1 ———	RED
2 ———	2 ———	WHITE
3 ———	3 ———	GREEN
4 ———	4 ———	BLACK
SHELL ———	SHELL ———	BRAID

4	USB A TYPE FEMALE SHELL PLATED NICKEL	1	PCS
3	UL2725 28AWG/1P+24AWG/2C+AEB REV. 2.0 IPOD WHITE IN COLOR OD4.7MM	1	PCS
2	PVC 55P IPOD WHITE IN COLOR		G
1	USB A TYPE MALE SHELL PLATED NICKEL	1	PCS
NO	DESCRIPTION	QTY	UNIT

RoHS Compliant

MORETHANALL
 CONNECTORS
 ASSEMBLIES

PART NO. UBX2-4A4A2VDK-E1M8

DWG NO. UBX2-4A4A2VDK-E1M8

CHECKED BY CY

TOLERANCES ARE

DESCRIP TION:

FILE NO.


DRAWING BY

.X ± 0.2
.XX ±
.XXX ±
AWG

UNIT / mm

SCALE 1:1

PROJECTION



AREA

REVISIONS

HK

DATE

煜倫股份有限公司