


WIRING CHART

A	COLOR	B
1	RED	1
2	WHITE	2
3	GREEN	3
4	BLACK	4
SHELL	BRAID	SHELL



NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5Ω Max
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY
1	WIRE:	UL 2725#28*1PR(WHITE, GREEN)+#20*2C(RED, BLACK)+AEB	1pcs
		USB 2.0 JACKET:BLACK OD:5.0	
2	CONN:	USB A TYPE MALE 4P WHITE INSULATION 30U"	1set
3	OUTMOLDED:	PVC 45P BLACK NO:GH-016	8.5G
4	CONN:	USB B TYPE MALE 4P WHITE INSULATION 30U"	1set
5	OUTMOLDED:	PVC 45P BLACK NO:GH-215	8.5G

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

PJECTION

照片框

ORDER INFORMATION

UBX2-4A4B2028-M6F-LF

SERIES

LEADFREE  
1830mm  
MALE TO MALE  
20.28 AWG  
4 PIN A TYPE TO 4 PIN B TYPE

DESCRIPTION: CABLE ASS"Y