



USB3.0

USB3.0 AM	USB3.0 AF	COLOR
1	1	RED
2	2	WHITE
3	3	GREEN
4	4	BLACK
5	5	YELLOW
6	6	BLUE
7	7	DRAIN
8	8	ORANGE
9	9	PURPLE
SHELL	SHELL	BRAID

**ELECTRICAL PROPERTIES:**

1. 100% OPEN SHORT MIS-WIRE TEST
2. Contact Resistance:10ohm.
3. Insulation Resistance:5Mega ohm.
4. Hipot test:300V/10ms.

4	55P PVC MOLD BLUE IN COLOR	1	pcs
3	USB3.0 A TYPE FEMALE SHELL PLATED:NICKEL CONTACT:G/F	1	pcs
2	USB3.0 A TYPE MALE SHELL PLATED:NICKEL CONTACT:G/F	1	pcs
1	UL20276 (1P*28#+D+AL+Myα1r)*2C+1P*28#+2C*28#+AL+B DD:5.5±0.15mm BLUE IN COLOR	1	pcs
NO.	DESCRIPTION	Q'TY	UNIT

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

PPOJECTION

照片框

**ORDER INFORMATION**

UBX2-9A9A28-E1M8-LF

SERIES | LEADFREE  
1800mm  
MALE TO FEMALE  
28 AWG  
9 PIN A TYPE TO 9 PIN A TYPE

DESCRIPTION: 3.0 USB CABLE L:1.5M BLUE

煜倫股份有限公司

www.morethanall.com