



ELECTRICAL PROPERTIES:

1. 100% OPEN SHORT MIS-WIRE TEST
2. Contact Resistance:10ohm
3. Insulation Resistance:5Mega ohm
4. Hipot test:DC 300V/10ms

USB3.0

USB3.0 AM	USB3.0 BM	OODOR
1	1	RED(PWR)
2	2	WHITE(UTP_D-)
3	3	GREEN(UTP_D+)
4	4	BLACK(GND_PWRrt)
5	5	YELLOW(SDP1-)
6	6	BLUE(SDP1+)
7	7	DRAIN(SDP1_Drain) (SDP2_Drain)
8	8	ORANGE(SDP2-)
9	9	PURPLE(SDP2+)
SHELL		SHELL Braid

4	55P PVC MOLD BLUE IN COLOR	1	pcs
3	USB3.0 B TYPE MALE SHELL PLATED:NICKEL CONTACT:G/F	1	pcs
2	USB3.0 A TYPE MALE SHELL PLATED:NICKEL CONTACT:G/F	1	pcs
1	UL20276 (1P*28#+D+AL+Mya1r)*2C+1P*28#+2C*28#+AL+B OD:5.5±0.15mm BLUE IN COLOR	1	pcs
DESCRIPTION		Q'TY	UNIT

UBX2-9A9B-M1M8-LF
LEADFREE
RoHS Compliant

 煜倫股份有限公司	PART NO.UBX2-9A9B-M1M8		CHECKED BY CY	TOLERANCES ARE .X±0.2 .XX± .XXX± AWG	DESCRIP TION:	AREA	REVISIONS	HK	DATE
	DWG NO. UBX2-9A9B-M1M8								
FILE NO.		PROJECTION							
UNIT / mm		SCALE 1:1							