

USB3.0 BM	USB3.0 BM	ODDOR
1	1	RED(PWR)
2	2	WHITE(UTP_D-)
3	3	GREEN(UTP_D+)
4	4	BLACK(GND_PWRrt)
5	5	YELLOW(SDP1-)
6	6	BLUE(SDP1+)
7	7	DRAIN(SDP1_Drain) (SDP2_Drain)
8	8	ORANGE(SDP2-)
9	9	PURPLE(SDP2+)
SHELL	SHELL	BRAID

ELECTRICAL PROPERTIES:

- 100% OPEN SHORT MIS-WIRE TEST
- Contact Resistance:10ohm
- Insulation Resistance:5Mega ohm
- Hipot test:300V/10ms

QTY	UNIT	DESCRIPTION
4	pcs	USB3.0 B TYPE FEMALE SHELL PLATED:NICKEL CONTACT:G/F
3	pcs	55P PVC MOLD BLUE IN ODDOR
2	pcs	USB3.0 B TYPE MALE SHELL PLATED:NICKEL CONTACT:G/F
1	pcs	UL20276 (1P*28#+D+AL+Mya1r)*2C+1P*28#+2C*28#+AL+B OD:5.5±0.15mm BLUE IN ODDOR

UBX2-9B9B-M50C-LF  
LEADFREE

RoHS Compliant

**MORETHANALL**  
CONNECTORS  
ASSEMBLIES

PART NO.UBX2-9B9B-M50C

DWG NO. UBX2-9B9B-M50C

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2  
.XX ±  
.XXX ±  
AWG

DESCRIPTION:

AREA

REVISIONS

HK

DATE

煜倫股份有限公司