



NOTE:

1. TEMPERATURE RANGE: -55°C TO +125°C.
2. CURRENT RATING: 21°C 2A, 71°C 1A, 110°C 0.5A
3. CONTACT RESISTANCE: 30 MILLIOHMS MAX. AT DC100mA
4. DIELECTRIC VOLTAGE: AC 1000V FOR 1 MINUTE
5. INSULATION RESISTANCE: 1000 MEGOHMS MIN. AT DC500V
6. OPERATING VOLTAGE: 250VAC

③	OPTIONAL	BOARD-LOCK : BRASS, 110µ" MIN. TIN PLATING
②	NO. OF POS.	CONTACT : BRASS, NICKEL PLATING OVER ALL AT 50 µ" MIN. SOLDER AREA PLATING: 110µ" MIN. TIN, CONTACT AREA PLATING GOLD
①	1	HOUSING : PBT UL94 V-1, COLOR GRAY
ITEM	Q'TY	DESCRIPTION

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4 PROJECTION

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

照片框

ORDER INFORMATION

UC-PD-2X32-LF
SERIES | LEADFREE
DIP 90° | 64 WAY
MALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: