



RECOMMENDED P.C. BOARD LAYOUT

NOTE:

1. TEMPERATURE RANGE: -55°C TO +125°C.
2. CURRENT RATING: 20°C 2A, 70°C 1A, 100°C 0.5A
3. CONTACT RESISTANCE: 30 MILLIOHMS MAX. AT DC100mA
4. DIELECTRIC VOLTAGE: AC 1000V FOR 1 MINUTE
5. INSULATION RESISTANCE: 1000 MEGOHMS MIN. AT DC500V
6. OPERATING VOLTAGE: 250VAC

③	OPTIONAL	BOARD-LOCK : BRASS, 100 μ" MIN. TIN PLATING
②	NO. OF POS.	CONTACT : BRASS, NICKEL PLATING OVER ALL AT 50 μ" MIN. SOLDER AREA PLATING: 100 μ" MIN. TIN, CONTACT AREA PLATING GOLD
①	1	HOUSING : PBT UL94V-0, COLOR GRAY
ITEM	Q'TY	DESCRIPTION

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

照片框

ORDER INFORMATION

UC-PDZ-3X16-LF  
SERIES | CLIP | LEADFREE  
48 WAY  
DIP 90°  
MALE

DESCRIPTION: