




NOTE:

1. WITHDRAWAL FORCE PER CONTACT: 0.115kg MIN.
2. TEMPERATURE RANGE: -55°C TO +125°C.
3. CURRENT RATING: 20°C 2A, 70°C 1A, 101°C 0.5A
4. CONTACT RESISTANCE: 30 MILLIOHMS MAX. AT DC100mA
5. DIELECTRIC VOLTAGE: AC 1000V FOR 1 MINUTE
6. INSULATION RESISTANCE: 1000 MEGOHMS MIN. AT DC500V
7. OPERATING VOLTAGE: 251VAC

④	OPTIONAL	BOARD-LOCK : BRASS, 100u" MIN. TIN PLATING
③	NO. OF POS.	CONTACT : PHOSPHOR BRONZE, NICKEL PLATING OVER ALL AT 50u" MIN. SOLDER AREA PLATING: 100u" MIN. TIN, CONTACT AREA PLATING GOLD
②	1	SPACER : PBT UL94V-0, COLOR GRAY
①	1	HOUSING : PBT UL94V-0, COLOR GRAY
ITEM	Q'TY	DESCRIPTION

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

TOLERANCES ARE

X. ±

.X ±

.XX ±

.XXX ±

ANG ±

PPOJECTION

照片框

ORDER INFORMATION

UC-SD-3X16-LF
SERIES | LEADFREE
DIP 180°
FEMALE

DESCRIPTION: