


RECOMMENDED P.C. BOARD LAYOUT



SEC A-A

NOTE:

1. WITHDRAWL FORCE PER CONTACT: 0.015kg MIN.
2. TEMPERATURE RANGE: -55°C TO +125°C.
3. CURRENT RATING: 20°C 2A, 70°C 1A, 100°C 0.5A
4. CONTACT RESISTANCE: 30 MILLIOHMS MAX. AT DC 100mA
5. DIELECTRIC VOLTAGE: AC 1000V FOR 1 MINUTE
6. INSULATION RESISTANCE: 1000 MEGOHMS MIN. AT DC 500V
7. OPERATING VOLTAGE: 250V AC

④	OPTIONAL	BOARD-LOCK : BRASS, 100u" MIN. TIN PLATING
③	NO. OF POS	CONTACT : PHOSPHOR BRONZE, NICKEL PLATING OVER ALL AT 5u" MIN SOLDER AREA PLATING: 10u" MIN. TIN, CONTACT AREA PLATING GOLD
②	1	SPACER : PBT UL94V-1, COLOR GRAY
①	1	HOUSING : PBT UL94V-1, COLOR GRAY
ITEM	Q'TY	DESCRIPTION

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±

.X, ±

.XX, ±

.XXX, ±

ANG, ±

PJECTION

照片框

ORDER INFORMATION

UC-SDZ-2X32-LF
SERIES LEADFREE
CLIP 64 WAY
DIP 180°
FEMALE

DESCRIPTION: