

P.C. Board Layout

Material:

Housing: Thermoplastic Polyester Glass Filled UL94V-0.

Contacts: Copper Alloy.

Electrical Characteristics:

Current Rating: 2 AMP.


Dielectric Withstanding Voltage: AC 1000V for 1 minute.

Insulator Resistance: 1000MΩ min. at DC 500V.

Contact Resistance: 20mΩ max. at DC 100mA.

Operating Temperature: -55°C~+125°C .

***RoHS Compliant**



Dip Type

Pitch	Position	Rows with Contacts	Contact Arrange	X length				P/N.
				Blank	02	13	17	
				4.0	2.5	13	17	
2.54mm	96	a b c						UC-SDxx-3X32
	64	a - c						UC-SDxx-2X32
	32	a - -						UC-SDxx-1x32
5.08mm	48	a b c						UC-SDxx-3x32E0
	32	a - c						UC-SDxx-2x32E0
	16	a - -						UC-SDxx-1x32E0

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±

.X, ±

.XX, ±

.XXX, ±

ANG ±

PPOJECTION

照片框

ORDER INFORMATION

UC-SDxx-xXxx-LF
SERIES P/N LEADFREE
FEMALE BLANK:4.0mm
02:2.5mm
13:13.0mm
17:17.0mm
DIP 180°

DESCRIPTION: