



Electrical Propeterties:

1. Conductor Resistance:
Max. 148 ohms/km at 20°
2. Insulation Resistance:
Min. 100 mega ohms/km at 20°
3. Dielectric Test:
2500 VAC/1min ; No Breakdown
4. Capacitance: Normal 55ph/m

Description:

Conductor:

1. Number of Conductor:8C
2. Material: Bare Copper Wire
3. Construction: 26 AWG (7/0.16mm)

Insulation:

1. Material: Polypropylene
2. Normal thickness: 0.23mm
3. Normal diameter: 0.95mm±0.05mm
4. Color code: Black

Jacket:

1. Material: PVC
2. Normal thickenss : 0.6mm
3. Normal diameter: 2.4 x 8.8±0.2

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PPOJECTION

照片框

ORDER INFORMATION

UL20251-26R1HFBK-08-LF
 SERIES | 26 AWG | BLACK | 08 WAY | LEADFREE
 1 ROLL 100FEET

DESCRIPTION: 26AWG*8C UL 20251 TELEPHONE CABLE