

Note:

1.Material:

- 1.1 Insulator: L.C.P UL 94-V0 rated.
- 1.2 Contact: Brass,t=0.25mm.
- 1.3 Shell: Cold rolled steel,t=0.30mm.

2.Specification:

- 2.1 Current rating: 1 A Max.
- 2.2 Dielectric withstanding voltage: 500 V(ac) for 1 minute.
- 2.3 Contact resistance: 30 m Ω Max.
- 2.4 Insulation resistance: 1000 m Ω Min at DC 500V.
- 2.5 Temperature range: -55°C~+105°C.

3.Finishes:

- 3.1 Contacts: Gold flashed 1u",3u",5u",10U",15u",30u".
- 3.2 Shell: Nickel plated.

USB-PDBK-4A-LF
LEADFREE
RoHS Compliant

3	SHELL	1	Cold rolled steel	T=0.30±0.02mm	Nickel Plated
2	CONTACT	4	Brass	T=0.25±0.02mm	Gold Flashed
1	HOUSING	1	LCP/ PBT		Black
No.	Part Name	Q'ty	Material	Thickness	Finish

MORETHANALL
CONNECTORS
ASSEMBLIES

煜倫股份有限公司

PART NO. USB-PDBK-4A

DWG NO. USB-PDBK-4A

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2
.XX ±
.XXX ±
AWG

DESCRIPTION:

USB-A MALE 180°直立式

AREA

REVISIONS

HK

DATE