



NOTE:

- 1.1 Contact resistance: 30 Mi Max
- 1.2 Insulation resistance: 1000 Mi min
- 1.3 Dielectric voltage: 500V AC one sec level
- 1.4 Operating temperature: -55°C ~ -105°C
- 1.5 Total mating force: 3.5 Kgf Max.
- 1.6 Total unmating force: 1.0 Kgf Min.
- 1.7 Major DIM: ∇

3	SHELL	Fe	T=0.30	Ni 80U		
2	TERMINAL	C5191H	T=0.25	Sn 100U* & Au		1
3	HOUSING	6T ROHS UL94V-0		WHITE/BLACK		
NO.	Part Name	MATERIAL	THICK	FINISH	Part NO	Q'TY

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

X. ± 0.50

CHECKED BY GENIUS

.X ± 0.20

UNIT / mm

SCALE 1 : 1

.XX ± 0.10

DATE

.XXX ±

ANG ±

SIZE A4

P PROJECTION



ORDER INFORMATION

USB-PWxx-4A-LF  
SERIES | | | LEADFREE  
4 PIN A TYPE  
BK:BLACK  
WH:WHITE  
90°SMT  
MALE

DESCRIPTION:

煜倫股份有限公司

www.morethanall.com