



RECOMMEND P. C. B LAYOUT COMPONENT

**SPECIFICATIONS**

**Electrical:**

- 1.Voltage Current Rating: 1.5 AMP, 30VAC
- 2.Contact Resistance: 30 mΩ Max
- 3.Insulation Resistance: 1,000 MΩ Min
- 4.Dielectric Withstanding Voltage: 500 V AC
- 5.Operating Temperature: -35°C ~ 85°C
- 6.Mating Force: 3.57 Kg Max
- 7.Umating Force: 1.02 Kg Min

**Material:**

- 1.Housing: PBT , UL 94V-0
- 2.Contact: Phosphor Bronze
- 3.Shell: Phosphor Bronze / Spcc

**Finish:**

- 1.Contact: Plated Gold in Mating Area ;  
Tin Plated on Solder Balls ;  
Nickel under plated overall
- 2.Shell: Nickel under Plated surface layer

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY  
CHECKED BY GENIUS  
UNIT / mm SCALE 1 : 1  
DATE

Up to 5 ±0.2  
Above 5 ~ 15 ±0.3  
Above 15 ~ 30 ±0.4  
Above 30 ~ 50 ±0.5  
Angle ±0.3°

照片框

**ORDER INFORMATION**

USB-SRF38FX14cc-4A-LF  
SERIES | LEADFREE  
FEMALE | 4 PIN A TYPE  
DIP 90° | BK:BLACK  
OFFSET 3.8mm | WH:WHITE  
NON FLANGE | LONG 14.20mm

煜倫股份有限公司

www.morethanall.com

SIZE A4 PROJECTION

DESCRIPTION: USB A/F 沉板H: 3.8mm 無捲邊