



MATERIALS

HOUSING: PBT (UL 94V-0)
SHELL: SPCC, NICKEL PLATING
TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA
TIN PLATING ON SOLDER TAIL

SPECIFICATION

CURRENT RATING: 1.5 AMP MAX
DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
CONTACT RESISTANCE: 30m OHMS MAX
INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V
OPERATION TEMPERATURE: -40°C~+85°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1:1

DATE

SIZE A4

X: ± 0.40
.X: ± 0.30
.XX: ± 0.20
.XXX: ± 0.10
ANG ±

PJECTION

照片框

ORDER INFORMATION

USB-SRFXZ68xx-4A-LF
SERIES | | | | LEADFREE
FEMALE | | | | 4 PIN A TYPE
DIP 90° | | | | BK:BLACK
NON FLANGE CLIP/2 | | | | WH:WHITE
HIGH 6.8mm

DESCRIPTION: USB A TYPE, PCB MOUNT, R/A, METAL SHIELD, FEMALE