



SECTION B-B

Pin #	SIGNAL NAME	DESCRIPTION	MAKING SEQUEN
1	VBUS	POWER	SECOND
2	D-	USB 2.0 DIFFERENTIAL PAIR	THIRD
3	D+		
4	GND	GROUND FOR POWER RETURN	SECOND
5	StdA_SSR	SUPERSPEED RECEIVER DIFFERENTIAL PAIR	LAST
6	StdA_SSRX+		
7	GND_DRAIN	GROUND FOR SIGNAL RETURN	
8	StdA_SSTX-	SUPERSPEED TRANSMITTER DIFFERENTIAL PAIR	
9	StdA_SSTX+		
Shell	Shield	CONNECTOR METAL SHELL	FRIST

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

X, ±

CHECKED BY GENIUS

.X ± 0.30

UNIT / mm

SCALE 1 : 1

.XX ± 0.20

DATE

.XXX ± 0.10

ANG ±

SIZE A4

PJECTION

照片框

ORDER INFORMATION

USB-SRRVF23MML-9A-LF  
SERIES | | | | | | | | | LEADFREE  
FEMALE | | | | | | | | | 9 PIN A TYPE  
DIP 90° | | | | | | | | | BLUE  
REVERSED | | | | | | | | | METAL FOOT  
2.39mm  
OFFSET

DESCRIPTION: USB 3.0 9P DIP 沉板 2.75

煜倫股份有限公司

www.morethanall.com