



Recommend P. C. B Layout

SPECIFICATIONS:

Contact current Rating:1Amperes.

DIELECTRIC Withstanding Voltage:AC 750V
at sea level

Insulation resistance:1000Megohms Minimum.

Contact Resistance:30mΩ Max

operating Temperature:-55° to+85°

MECHANICAL CHARACTERISTICS:

Mating Force:3.5Kg. Maximum

Unmating Force:1kg. Mlimum.

3	胶蕊	1	PBT 30%G		COLOR: WHITE/BLACK
2	端子	4	C5191H	NICKEL PLATED OVER ALL TIN/GOLD PLATING	80u" GOLD/1-30u"
1	外壳	1	黄铜	Ni/Sn PLATING	
序号	名称	数量	材料	表面	备注

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X ± 0.30

CHECKED BY GENIUS

.X ± 0.25

UNIT / mm

SCALE 1 : 1

.XX ± 0.20

DATE

.XXX ± 0.10

ANG ± 5°

SIZE A4

PPOJECTION

照片框

ORDER INFORMATION

USB-SRRVF35EZ2xx-4A-LF

SERIES | | | | | LEADFREE
FEMALE | | | | | 4 PIN A TYPE
DIP 90° | | | | | BK:BLACK
REVERSED | | | | | WH:WHITE
OFFSET 3.5mm

DESCRIPTION:

煜倫股份有限公司

www.morethanall.com