



PCB LAYOUT

NOTES:

Housing: Thermoplastics,UL94V-0
 Contact: Copper Alloy
 Shell: Copper Alloy/Steel
 Voltage Current Rating:1.5 AMP. 30V AC
 Insulation Resistance:1000M Ω Min.
 Contact Resistance:30 M Ω Max.
 Dielectric Withstanding Voltage:500W AC
 Temperature Range:-35°C to +85°C
 Insulator color: Black/White
 Plastic material:PBT/LCP/Others
 Shell finish:Nickel plated/Tin-Lead plated
 Mechanical:
 Mating Force: 3.5KG MAX
 Unmating Force: 0.7 KG MIN.

Contact pin: Gold Flash

RoHS Compliant

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT/ mm SCALE 1:1

DATE

SIZE A4

TOLERANCES ARE

X. ± 0.30
 .X ± 0.25
 .XX ± 0.20
 .XXX ± 0.10
 ANG ± 5°

P PROJECTION

照片框

ORDER INFORMATION

USB-SRRVZcc-4A-LF
 SERIES | LEADFREE
 | 4 PIN A TYPE
 | BK:BLACK
 | WH:WHITE
 FEMALE | CLIP
 DIP 90° | REVERSED

DESCRIPTION: USB A FEMALE RIGHT ANGLE(反向90°)