



MATERIALS

HOUSING: HI-TEMP. PLASTIC WHITE OR BLACK (UL 94V-0)
 SHELL: SPCC OR COPPER ALLOY, NICKEL PLATING
 TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA
 TIN PLATING ON SOLDER TAIL

SPECIFICATION

CURRENT RATING: 1 AMP MAX
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -25°C~+85°C



煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY
 CHECKED BY GENIUS
 UNIT / mm SCALE 1 : 1
 DATE
 SIZE A4 PPROJECTION

TOLERANCES ARE

X. ±
 .X ± 0.25
 .XX ± 0.15
 .XXX ± 0.05
 ANG ±

照片框

ORDER INFORMATION

USB-SRZ113BK100FX-4A-LF
 SERIES LEADFREE
 4 PIN A TYPE
 NON FLANGE
 LONG 10.0mm
 FEMALE
 DIP 90° CLIP BLACK FOOTPRINT 1.35mm

DESCRIPTION: